



## Built to last

Sturdy industrial-strength designed for continuous high-traffic operation.



## Stay Connected

With two SIM slots and an eSIM, the MAX Adapter always has a way to connect.

## Compatible with 5G

MAX Adapter now offers a 5G compatible device option. Bringing 5G connectivity to your devices.

**MAX ADAPTER**  
State-of-the-art Cellular Modem at a breakthrough price point



## Portable

The light and sleek enclosure offers portability in the palm of your hands.



Connect with

peplink | PEPWAVE



## Peplink Products

Protect and reinforce products<sup>^</sup> with a USB port and make it a 5G/LTE WAN.

 [Learn More](#)

OR

## Windows & Linux\* Devices

Providing 5G/LTE connectivity for Windows and Linux devices on-the-go.



<sup>^</sup> For compatible models, please refer to the MAX Adapter [FAQ](#).

\* For users on the Linux, please refer to our MAX Adapter user manual to set up.

peplink | PEPWAVE

[www.peplink.com](http://www.peplink.com)

©Peplink. All rights reserved.

# MAX Adapter 5G



## Specifications

Cellular WAN Interfaces	Single 5G Modem	Operating Temperature	32° – 104°F / 0° – 40°C
Redundant SIM Slot	Yes	Humidity	15% – 95% (non-condensing)
Downlink/Uplink Datarate	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps	Warranty	1-Year Limited Warranty
Antenna Connectors	4x SMA Cellular	Certifications	FCC, CE, IC
Power Input	5V USB-C	Package Content	MAX Adapter 5G, 4x LTE/5G LTE Antennas (ACW-235), USB-C Female to USB-A Male Adapter, USB-C Power Cable
Power Consumption	5W (nominal), 8W (max.)	US Carrier Certifications	AT&T, T-Mobile, US Cellular
Dimensions	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm		
Weight	120g		

## Ordering information

Product Code	Carrier / Category	5G Bands	LTE Bands
MAX-ADP-5GH-T	Global / 5G	<b>5G (NSA) Sub 6Ghz:</b> n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32,B34, B38, B39, B40, B41, B42, B46, B48, B66, B71



## Specifications

<b>Cellular WAN Interfaces</b>	Single LTE Modem	<b>Weight</b>	120g
<b>Redundant SIM Slot</b>	Yes	<b>Operating Temperature</b>	32° – 104°F / 0° – 40°C
<b>Downlink/Uplink Datarate</b>	CAT-12: 600 Mbps / 150 Mbps CAT-6: 300Mbps / 50Mbps	<b>Humidity</b>	15% – 95% (non-condensing)
<b>Antenna Connectors</b>	2x SMA Cellular, 1x SMA GPS	<b>Warranty</b>	1-Year Limited Warranty
<b>Power Input</b>	5V USB-C	<b>Certifications</b>	FCC, CE, IC
<b>Power Consumption</b>	5W (nominal), 8W (max.)	<b>Package Content</b>	MAX Adapter, 2x LTE Antennas (ACW-813), USB-C Female to USB-A Male Adapter, USB-C Power Cable
<b>Dimensions</b>	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm	<b>US Carrier Certifications</b>	Verizon, AT&T

## Ordering information

Product Code	Carrier / Category	LTE Bands	3G Bands
MAX-ADP-LTEA-K-T	Global CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B18, B19, B20, B26, B28, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-R-T	America CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B18, B19, B20, B26, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-W-T	Global CAT-6	B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41	WCDMA/HSPA+/DC-HSPA+: B1, B2, B3, B4, B5, B8

## Accessories

Product Code	Description
ACW-232	GPS Antenna